MATERIAL SAFETY DATA SHEET

SULLIVAN SUPPLY, INC.
701 IOWA AVE.
DUNLAP, IA 51529

INFORMATION TELEPHONE NO.: 712-643-5902
EMERGENCY TELEPHONE NO.: 800-255-3924

PREPARATION DATE: 6/12/02 PREPARER: SCOTT KINZER

SECTION I - PRODUCT IDENTIFICATION

SUDDEN IMPACT S/S

SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NUMBER
PROPANE	74-98-6
ISOBUTANE	75-28-5
N-BUTANE	106-97-8

N/A = NOT APPLICABLE

SECTION III - PHYSICAL DATA

BOILING RANGE: NOT ESTABLISHED
ODOR : MUSK
APPEARANCE : OFF WHITE
SOLUBILITY: NEGLIGIBLE
VAPOR PRESSURE: < 1
VAPOR DENSITY: < 1
EVAPORATION RATE: < 1
VISCOSITY: THIN
SPECIFIC GRAVITY : N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATE

FLAMMABILITY CLASS: FLASH POINT: -50% PROPELLENT LEL: 1.8% UEL: 9.5%
EXTINGUISHING MEDIA: WATER, CO2
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, NITROGEN. SMALL AMOUNTS OF HYDROGEN CHLORIDE, PHOSGENE

FIREFIGHTING PROCEDURES: WATER FOG MAY BE USEFUL IN HELPING COOL THE CANS TO PREVENT OVERPRESSURIZATION AND EXPLOSION. WEAR SELF CONTAINED BREATHING APPARATUS. BURSTING CANS MAY TRAVEL GREAT DISTANCES SPEWING VOLATILE MATERIAL. VAPORS ARE HEAVIER THAN AIR AND WILL TRAVEL GREAT DISTANCES TO POINTS OF IGNITION. USE CAUTION WHEN VENTILATING AREAS WHEN CANS HAVE RUPTURED.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVER EXPOSURE: EYES: CAN CAUSE IRRITATION, IRRIGATE WITH FLOWING WATER AT LEAST 10 MINUTES. HOLD LIDS OPEN AS IT ALLOWS THE SOLVENT TO EVAPORATE AND MINIMIZE IRRITATION. SEEK MEDICAL ATTENTION AS MATERIAL MAY BECOME IMBEDDED. SLIGHT CHANCE FOR TRANSIENT CORNEAL DAMAGE.

SKIN: CAN CAUSE IRRITATION, DEFATTING, DERMITITUS. WASH WITH SOAP AND WATER.

SWALLOWING: DO NOT INDUCE VOMITING. CALL A PHYSICIAN AND OR POISON CONTROL CENTER IMMEDIATELY. IF ASPIRATED LIQUID MAY BE ABSORBED THROUGHT THE LUNGS AND RESULT IN SYSTEMATIC EFFECTS.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT GIVE OXYGEN. CALL A PHYSICIAN AS EXCESSIVE EXPOSURE TO THE RAW MATERIALS USED IN THIS PRODUCT HAS BEEN FOUND TO TARGET THE CENTRAL NERVOUS SYSTEM.

SECTION VI - REACTIVITY DATA

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS

INCOMPATIBALITY: EXTREME HEAT, SOURCES OF IGNITION.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBANT, OR OTHER ABSORBANT MATERIAL AND TRANSFER TO HAZARDOUS WASTE DRUM. USE NON SPARKING TOOLS WHEN REMOVING WET ABSORBANT. LARGE SPILLS: DIKE AREA, PUT LIQUID INTO SALVAGE DRUM. ABSORB REMAINING. PREVENT RUNOFF TO SEWERS, STREAMS OR OTHER BODIES OFW ATER. IF RUNOFF OCCURS, NOTIFY AUTHORITIES AS REQUIRED.

WASTE DISPOSAL METHOD: SMALL SPILL: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK. DISPOSE OF REMAINING MATERIAL IN ACCORDANCE WITH APPLICABLE REGULATIONS. LARGE SPILL: DESTROY BY LIQUID INCINERATION WITH OFF-GAS SCRUBBER. CONTAMINATED ABSORBANT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: NIOSH/OSHA APPROVED RESPORATOR TYPES SUITABLE FOR MATERIALS IN SECTION II RECOMMENDED. APPROVED CHEMICAL/MECHANICAL FILTERS RECOMMENDED WHEN VENTILATION IS RESTRICTED.

VENTILATION: SUFFICIENT VENTILATION, IN VOLUME AND PATTERN, SHOULD BE PROVIDED TO KEEP AIR CONTAMINATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMIT OR ACGHI'S TLV LIMIT.

PROTECTIVE GLOVES: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT. WEAR RESISTANT GLOVES SUCH AS POLYVINYL ALCOHOL, POLYETHYLENE.

EYE PROTECTION: CHEMICAL GOGGLES WITH SIDE SHIELDS OR FACE SHIELD RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS COLTHING AND BOOTS.

HYGENIC PRACTICES: WASH HANDS BEFORE EATING OR SMOKING.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: DO NOT STORE AEROSOL CONTAINERS ABOVE 120 DEGREES F. DO NOT DISPOSE OF AEROSOLS IN FIRES OR TRASH COMPACTORS.
OTHER PRECAUTIONS:none

SECTION X - HMIS RATING

HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1 PERSONAL PROTECTION: H

SECTION XI - TRANSPORTATION AND STORAGE

TRANSPORTATION AND STORAGE: DOT CLASSIFICATION: FLAMMABLE GAS UN-1954
DOT LABELING/PLACARD: CONSUMER COMMODITY ORM-D
PROPER SHIPPING NAME: COMPRESSED GAS N.O.S.
PROPELLANT: PROPANE/ISOBUTANE
CONTAINER SIZE: 12/ 17 OZ. NET WT.
UNIT WT.: 18 LBS PER CASE OF 12
SARA III REPORTABLE QUANTITY: 1000 LBS
NFPA 30 B CLASSIFICATION: LEVEL 3

SECTION XII - OTHER REGULATORY INFORMATION

OTHER REGULATORY INFORMATION: THIS PRODUCT IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III. DISCLAIMER: THE FOREGOING INFORMATION HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT DATA IS CORRECT. STANDARDS CHANGE WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE RECIPIENT TO ASSURE THAT THEIR PERSONNEL HAVE BEEN NOTIFIED OF ANY CHANGES WHICH MAY AFFECT THEM. THE DATA PROVIDED ON THIS MSDS ARE NOT MEANT TO BE USED AS SPECIFICATIONS, ONLY AS GUIDELINE INFORMATION AS TO THE SAFE USE OF THE PRODUCT. USER SHOULD REFER TO APPLICABLE LAWS BEFORE USE.

PROPOSITION 65 STATEMENT: THIS PRODUCT CONTAINS SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR BE A REPRODUCTIVE TOXIN. PROPOSITION 65.

THE INFORMATION CONTAINED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEE OF RESULTS, AND ASSUME

NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.