

QUICK-SLING


Quick-Sling Quick Swivel SPECS QSWI 3000



The flush mount hanger arm is slotted to receive a 5/16 lag bolt 16" or 24" on center. It can be attached parallel or perpendicular to the joist.



Our Quick Swivel is made with 14-gauge steel able to hold 200 lbs. The swivel allows for a 360° rotation for setting the perfect direction of air flow.



The square steel tubing cuts down on vibration while 3 hitch-pins add to the safety and sturdiness of the Quick Swivel with "H" bracket.



Installation can be accomplished in minutes because all necessary hardware is provided. Attaching a Quick Swivel to your unit is fast & stress-free.

The Quick Swivel can easily be installed in residential or commercial applications. Turn the Swivel in any direction you need then lock it in place, it's that quick.

Patent Pending

Quick-Sling's Quick Swivel provides you with a non-swinging, rotating platform that is quick, safe, stable and affordable.

The safe & affordable install

Applicable for residential or light commercial installations



How would you hang a unit in this type of application, with unistrut & threaded rod?

How much time & energy would an installation like this take you?

Now try & get the perfect angle...OH NO!

We are glad to introduce to you Quick-Sling, LLC., a line of hangers & stands that provides a sturdy platform for furnaces & air-handlers within residential & light commercial use.

Our goal is to save you time & money so that YOU HAVE MORE TIME TO MAKE MORE MONEY.

Quick-Sling, LLC. – the HVAC installation that installs in minutes

The Quick-Sling Quick Swivel advantage:

- Installation is quick
- Passes inspections in all 50 states
- Quick-Sling is powder coated to last
- Provides a safe & secure foundation
- All necessary hardware is provided
- Fully rotational for the perfect direction

QUICK-SLING

391 West Water Street
Taunton, MA 02780
Phone: 1.800.699.0453
Fax: 1.800.699.0423
www.Quick-Sling.com